

Test Management: Part II

Software Testing: INF3121 / INF4121

Summary: Week 7

Test **organisation**

Independence | Tasks of the test leader and testers

Test **planning** and **estimation**

Activities | Entry and exit criteria | Estimation | Strategy and approach

Test **progress** monitoring and **control**

Configuration and **management**

Risk and testing



Part I: Close-ended questions

Question 1

Which of the following **metrics** would be most **useful** to **monitor** during **test execution**?

- a. Percentage of test cases written
- b. Number of test environments remaining to be configured
- c. Number of defects found and fixed
- d. Percentage of requirements for which a test has been written



Question 1: Answer

Which of the following **metrics** would be most **useful** to **monitor** during **test execution**?

Test **progress monitoring**

Give **feedback** and visibility of the **test effort** / activities

Monitoring **information** can be collected **manually** / **automatically**

Metrics can be used to measure **exit criteria**

Common test **metrics**

| | | | |
|--|---|--|--------------------------|
| % of work done in test case preparation | Test case execution (e.g. number of tests run/not run) | Defect information (e.g. defect density, found / fixed) | Dates of test milestones |
| % of work done in test environment preparation | Test coverage (requirements, risks, code) | Subjective confidence of testers in the product | Testing costs |

Question 1: Answer

Which of the following **metrics** would be most **useful** to **monitor** during **test execution**?

- a. Percentage of test cases written
- b. Number of test environments remaining to be configured
- c. Number of defects found and fixed**
- d. Percentage of requirements for which a test has been written



Question 2

In a test **summary report**, the project's test leader makes the following statement:

*“The payment processing **subsystem** fails to **accept payments** from American Express cardholders, which is considered a **must-work feature** for this release.”*

This statement is likely to be found in which **section**?

- a. Evaluation
- b. Summary of activities
- c. Variances
- d. Incident description

Question 2: Answer

This statement is likely to be found in which **section**?

Test **reporting**

Summarising information about the **test** effort

What happened during a test period?

E.g. dates when exit criteria were met

Analysed **metrics** to **support decisions** about future actions

Adequacy of the **test objectives** for that test level

Adequacy of the **test approaches** taken

Effectiveness of the **testing** with respect to its test objectives



Question 2: Answer

This statement is likely to be found in which **section**?

“The payment processing subsystem fails to accept payments from American Express cardholders, which is considered a must-work feature for this release.”

IEEE 829 Standard: TEST SUMMARY REPORT

Test summary report identifier

Summary

Identify all relevant support materials
Test items / Environment / References

Variations

Document changes or deviations from test plan

Comprehensiveness assessment

Evaluation of the test effort in terms of objectives
Assess quality / effectiveness of testing

Summary of results


Report overall status of incidents
Defect patterns / Open, unresolved incidents

Evaluation

Assess quality of the software
Limitations → Incomplete or partial functions
Failure likelihood

Summary of activities

Approvals



Question 2: Answer

In a test **summary report**, the project's test leader makes the following statement:

*“The payment processing **subsystem** fails to **accept payments** from American Express cardholders, which is considered a **must-work feature** for this release.”*

This statement is likely to be found in which **section**?

- a. **Evaluation**
- b. Summary of activities
- c. Variances
- d. Incident description

Question 3

During an **early** period of test **execution**, a **defect** is **located**, **resolved** and **confirmed** as resolved by **re-testing**, but is seen again later during **subsequent** test execution.

Which of the following is a **testing-related** aspect of **configuration management** that is most likely to have **broken** down?

- a. Traceability
- b. Confirmation testing
- c. Configuration control
- d. Test documentation management



Question 3: Answer

Which is a **testing-related** aspect of **configuration management** most likely to have **broken down**?

Configuration Management

Establish and maintain the integrity of the products of the software

Components

Data

Documentation

Integrity → Assurance of the **accuracy** and **consistency** of data through the life cycle

Ensure that **all items** of **testware** are:

Identified

Version controlled

Tracked



Maintain **traceability**
throughout the test **process**



Question 3: Answer

During an **early** period of test **execution**, a **defect** is **located**, **resolved** and **confirmed** as resolved by **re-testing**, but is seen again later during **subsequent** test execution.

Which of the following is a **testing-related** aspect of **configuration management** that is most likely to have **broken** down?

- a. Traceability
- b. Confirmation testing
- c. Configuration control**
- d. Test documentation management



Question 4

You are working as a tester on a project to **develop** a **point-of-sales** system for grocery stores. Which of the following is a **product risk** for such a project?

- a. Arrival of a more reliable competing product on the market
- b. Delivery of an incomplete test release to the first cycle of system test
- c. An excessively high number of defect fixes fail during re-testing
- d. Failure to accept allowed credit cards

Question 4: Answer

Which of the following is a **product risk** for a **point-of-sales** system?

Risks

Possibility of a **negative** / undesirable **outcome**

Possible **problems** that may **endanger** the **objectives** of the **project** stakeholders

Risk **analysis** and **management** aid in **managing** possible negative **outcomes**

Two main **categories** of risks

Product risks

Project risks



Question 4: Answer

Which of the following is a **product risk** for a **point-of-sales system**?

Product Risks

Potential failure areas in the software

Risks specifically related to the **quality** of the **product**

Failure-prone software

Software / Hardware that **could cause harm** to the user

Poor software **characteristics**

Software that does **not perform** its **intended** functions



Question 4

You are working as a tester on a project to **develop** a **point-of-sales** system for grocery stores. Which of the following is a **product risk** for such a project?

- a. Arrival of a more reliable competing product on the market
- b. Delivery of an incomplete test release to the first cycle of system test
- c. An excessively high number of defect fixes fail during re-testing
- d. Failure to accept allowed credit cards**

Question 5

A **product risk analysis** meeting is held during the **planning** period. Which of the following **determines** the **level of risk**?

- a. Difficulty of fixing related problems in code
- b. The harm that might result to the user
- c. The price for which the software is sold
- d. The technical staff in the meeting


Question 5: Answer

What **determines** the **level** of **risk** during a **product risk analysis** meeting in the **planning** period?

Determining the level of risk

Likelihood → What are the **chances**?

Impact → What are the **consequences**?



Question 5

A **product risk analysis** meeting is held during the **planning** period. Which of the following **determines** the **level of risk**?

- a. Difficulty of fixing related problems in code
- b. The harm that might result to the user**
- c. The price for which the software is sold
- d. The technical staff in the meeting

Question 6

You are writing a **test plan** using the **IEEE 829** template and currently completing the **Risks** and **Contingencies** section.

Which of the following is most likely to be listed as a **project risk**?

- a. Unexpected illness of a key team member
- b. Excessively slow transaction-processing time
- c. Data corruption under network congestion
- d. Failure to handle a key use case

Question 6: Answer

Which of the following is most likely to be listed as a **project risk**?

Project risks

Risks that surround the project's capability to deliver its objectives

Risks specifically related to **aspects** of the **project processes**

Organisational factors

Shortage of people, skill, training | Communication and attitude problems

Technical issues → Problems defining the right requirements

Supplier issues → Third-party failures



Question 6: Answer


You are writing a **test plan** using the **IEEE 829** template and currently completing the **Risks** and **Contingencies** section.

Which of the following is most likely to be listed as a **project risk**?

- a. **Unexpected illness of a key team member**
- b. Excessively slow transaction-processing time
- c. Data corruption under network congestion
- d. Failure to handle a key use case

Question 7

You and the project stakeholders **develop** a **list** of **product** risks and **project risks** during the **planning** stage of a project. What **else** should you **do** with those **lists** of **risks** during test **planning**?

- a. Determine the extent of testing required for the product risks and the mitigation and contingency actions required for the project risks
 - b. Obtain the resources needed to completely cover each product risk with tests and transfer responsibility for the project risks to the project manager
 - c. Execute sufficient tests for the product risks, based on the likelihood and impact of each product risk and execute mitigation actions for all project risks
 - d. No further risk management action is required at the test planning stage
- 

Question 7: Answer

What **else** should you **do** with those lists of **product** and **project risks** during test **planning**?

Risk-based **approach** during the **planning** stage

Product risks

Determine the **extent** of **testing** to be carried out

Prioritise testing in an attempt to **reveal** critical **defects** as **early** as possible

Project risks

Identify risk items


Determine **likelihood** and **impact** for each item

Define **mitigation** and **contingency** actions for the identified risks



Question 7: Answer

You and the project stakeholders **develop** a **list** of **product** risks and **project risks** during the **planning** stage of a project. What **else** should you **do** with those **lists** of **risks** during test **planning**?

- a. **Determine the extent of testing required for the product risks and the mitigation and contingency actions required for the project risks**
 - b. Obtain the resources needed to completely cover each product risk with tests and transfer responsibility for the project risks to the project manager
 - c. Execute sufficient tests for the product risks, based on the likelihood and impact of each product risk and execute mitigation actions for all project risks
 - d. No further risk management action is required at the test planning stage
- 

Question 8

According to the **ISTQB Glossary**, a **product risk** is related to which of the following?


- a. Control of the test project
- b. The test object
- c. A single test item
- d. A potential negative outcome



Question 8: Answer

According to the **ISTQB Glossary**, a **product risk** is related to which of the following?

Product risk: ISTQB definition



In **contrast** to a **project risk**

"A *risk* related to *management* and *control* of the *project* "

E.g. lack of staffing, strict deadlines, changing requirements, etc.

Question 8: Answer

According to the **ISTQB Glossary**, a **product risk** is related to which of the following?

- a. Control of the test project
- b. The test object**
- c. A single test item
- d. A potential negative outcome



Question 9

Typical **test strategies** include:

1. **Risk-based** testing
Testing directed to areas of greatest risk
2. **Failure-based** testing
Test more in failure-prone areas
3. **Management-directed** testing
Test first the areas indicated by the org. management

Which are **true** and which are **false**?



Question 9: Answer

Risk-based testing

Idea: Can **organise** test **effort** to **reduce** the residual level of **risk**

Use of risk **analysis** to **prioritise** and **emphasise** appropriate tests

Guide **planning**, **specification**, **preparation**, and **execution**

Analysis and risk identification starts **early** in the project

Involves both **preventive** (mitigation) and **damage control** (contingency) **measures**

Mitigation → Testing to provide opportunities to reduce likelihood of defects

Contingency Testing to identify work-arounds for the defects that aren't discovered



Question 9: Answer

Failure-based testing

Idea: Can **organise** test **effort** based on **failure-prone** areas

Identifies **areas** most **likely** to hold **defects**, based on **complexity**

Some **functionality** is **harder** to **implement** than other

These areas are more **vulnerable** to defects

Starts **early** in the project and conducted **throughout** the **life** cycle

New problems / challenges will always emerge

Management-directed testing

This is **not** a defined test **strategy** in the ISTQB syllabus



Question 9: Answer

Typical **test strategies** include:

1. **Risk-based** testing **TRUE**

Testing directed to areas of greatest risk

2. **Failure-based** testing **TRUE**

Test more in failure-prone areas

3. **Management-directed** testing **FALSE**

Test first the areas indicated by the org. management

Which are **true** and which are **false**?



Question 10

In an **incident report**, the tester makes the following statement:

"At this point, I expect to receive an error message explaining the rejection of this invalid input and asking me to enter a valid input. Instead, the system accepts the input, displays an hourglass for between one and five seconds, and finally terminates abnormally, giving the message [Unexpected data type: 15. Click to continue]"

This **statement** is likely to be **found** in which of the following **sections** of an **IEEE 829** Incident Report?

- a. Summary
- b. Impact
- c. Item pass / fail criteria
- d. Incident description




Question 10: Answer

This **statement** is likely to be **found** in which of the following **sections** of an **IEEE 829** Incident Report?

“At this point, I expect to receive an error message explaining the rejection of this invalid input and asking me to enter a valid input. Instead, the system accepts the input, displays an hourglass for between one and five seconds, and finally terminates abnormally, giving the message [Unexpected data type: 15. Click to continue]”

| IEEE 829 Standard: TEST INCIDENT REPORT |
|---|
| Test incident report identifier |
| Summary Summary of actual incident References to: Test procedure used to discover incident Test logs showing actual execution of cases |
| Incident description Detailed explanation of the incident Inputs / Expected results Actual results Anomalies Procedure step |
| Impact Report actual damage caused by incident Severity / Priority assessment |



Question 10: Answer

In an **incident report**, the tester makes the following statement:

"At this point, I expect to receive an error message explaining the rejection of this invalid input and asking me to enter a valid input. Instead, the system accepts the input, displays an hourglass for between one and five seconds, and finally terminates abnormally, giving the message [Unexpected data type: 15. Click to continue]"

This **statement** is likely to be **found** in which of the following **sections** of an **IEEE 829** Incident Report?

- a. Summary
- b. Impact
- c. Item pass / fail criteria
- d. Incident description**



Question 11

According to the **ISTQB Glossary**, what do we call a **document** that describes **any event** that **occurred** during **testing** which requires **further investigation**?

- a. A bug report
- b. A defect report
- c. An incident report
- d. A test summary report



Question 11: Answer

According to the **ISTQB Glossary**, what do we call a **document** that describes **any event** that **occurred** during **testing** which requires **further investigation**?

Incident

Discrepancies between **actual** and **expected** test **outcomes**

Incident management

The process of **recognising**, **investigating**, taking **actions**, and **disposing** of incidents

Incident report

A **document** reporting on **any event** that occurred during testing

Requires **further investigation**

A decorative horizontal bar at the bottom of the slide consisting of a series of grey chevrons pointing to the right. The final chevron on the right is a solid dark grey circle.

Question 11: Answer

According to the **ISTQB Glossary**, what do we call a **document** that describes **any event** that **occurred** during **testing** which requires **further investigation**?

- a. A bug report
- b. A defect report
- c. An incident report**
- d. A test summary report



Question 12

A **product risks analysis** is performed during the **planning** stage of the test process. During the **execution** stage, the test manager directs testers to **classify** each **defect** report by the **known product risk** it relates to (or by '**other**').

Once a week, the test manager runs a **report** that **shows** the percentage of **defects** related to each **known product risks**, and to **unknown risks**.

What is one **possible use** of such a **report**?

- a. To identify new risks to system quality
- b. To locate defect clusters in product subsystems
- c. To check risk coverage by tests
- d. To measure exploratory testing

Question 12: Answer

What is one **possible use** for a **report** showing **defects** related to **known** product risks and **unknown risks**?

Objectives of an **incident** report

Provide **developers** with feedback about incidents to:

Enable **identification**, **isolation**, and **corrective** measures

Provide **test leaders** with feedback about incidents to:

Track system **quality**

Measure test **progress**

Provide **ideas** for test process **improvement**

Identify potential **new risks** to system quality



Question 12: Answer

A **product risks analysis** is performed during the **planning** stage of the test process. During the execution stage, the test manager directs testers to **classify** each **defect** report by the **known product risk** it relates to (or by '**other**').

Once a week, the test manager runs a **report** that **shows** the percentage of **defects** related to each **known product risks**, and to **unknown risks**.

What is one **possible use** of such a **report**?

- a. **To identify new risks to system quality**
- b. To locate defect clusters in product subsystems
- c. To check risk coverage by tests
- d. To measure exploratory testing



Part II: Exercises and Open-ended questions

Exercise 1

Go to the following **website** and **find** an **incident**:

www.adam.goucher.ca/parkcalc/

Fill out the attached **incident report**



Exercise 1: Incident Report

Date: _____

Project: _____

Tester: _____

Program / Module: _____ Build/Revision/Release: _____

Software Environment: _____ Hardware Environment: _____

Status of the incident: _____

Number of Occurrences: _____ Severity: _____ Impact: _____ Priority: _____

Detailed Description: _____

Expected result / Actual result: _____

Assigned To: _____

Incident Resolution: _____



Exercise 1: Incident Report


Date: 24.02.16
Project: adam.goucher.ea /parkCalc
Tester: Esben

Program/Module: Parking Calculator Build/Revision/Release: _____
Software Environment: Vivaldi 1.0.544.37 Hardware Environment: Macbook Pro
Status of the incident _____

Number of Occurrences: 2 Severity: low Impact low Priority low
Detailed Description: When choosing lot Long-term Garage parking,
and entry time is after exit time, you don't get
an error message, just cost = 0, and a negative time displayed

Expected result / Actual result: Error message expected,
but 0, and negative time is given as result.

Assigned To: Uncle Bob
Incident Resolution: _____



The seminar slides are made by

Yulai Fjeld

ydfjeld @ uio.no

Master student

Department of Informatics

University of Oslo

Previously taught courses

Systemutvikling (INF1050), Universitet i Oslo

Software Testing (INF3121/4121), Universitetet i Oslo

Systemutvikling (ADSE2200), Høgskolen i Oslo og Akershus

