

INF 4300 2015

Object feature extraction – shape descriptors

Exercise 1. Matlab exercise for recognition of round objects

Step 1: Read Image

```
Read in pills_etc.png.  
RGB = imread('pillsetc.png');  
imshow(RGB);
```

Step 2: Threshold the Image

Convert the image to black and white in order to prepare for boundary tracing using `bwboundaries`.

```
I = rgb2gray(RGB);  
threshold = graythresh(I);  
bw = im2bw(I,threshold);  
imshow(bw)
```

Step 3: Remove the Noise

Using morphology functions, remove pixels which do not belong to the objects of interest.

```
% remove all object containing fewer than 30 pixels  
bw = bwareaopen(bw,30);  
% fill a gap in the pen's cap  
se = strel('disk',2);  
bw = imclose(bw,se);  
% fill any holes, so that regionprops can be used to estimate  
% the area enclosed by each of the boundaries  
bw = imfill(bw,'holes');  
imshow(bw);
```

Step 4: Find the Boundaries

Concentrate only on the exterior boundaries. Option 'noholes' will accelerate the processing by preventing `bwboundaries` from searching for inner contours.

```
[B,L] = bwboundaries(bw,'noholes');  
% Display the label matrix and draw each boundary  
imshow(label2rgb(L, @jet, [.5 .5 .5]))  
hold on  
for k = 1:length(B)  
    boundary = B{k};  
    plot(boundary(:,2), boundary(:,1), 'w', 'LineWidth', 2)  
end
```

Step 5: Determine which Objects are Round

Estimate each object's area and perimeter. Use these results to form a simple metric indicating the roundness of an object:

```
metric = 4*pi*area/perimeter^2.
```

This metric is equal to one only for a circle and it is less than one for any other shape. The discrimination process can be controlled by setting an appropriate threshold. In this example use a threshold of 0.94 so that only the pills will be classified as round.

Use `regionprops` to obtain estimates of the area for all of the objects. Notice that the label matrix returned by `bwboundaries` can be reused by `regionprops`.

```
stats = regionprops(L,'Area','Centroid');  
threshold = 0.94;  
  
% loop over the boundaries  
for k = 1:length(B)  
    % obtain (X,Y) boundary coordinates corresponding to label 'k'  
    boundary = B{k};  
    % compute a simple estimate of the object's perimeter
```

```

    delta_sq = diff(boundary).^2;
    perimeter = sum(sqrt(sum(delta_sq,2)));
    % obtain the area calculation corresponding to label 'k'
    area = stats(k).Area;
    % compute the roundness metric
    metric = 4*pi*area/perimeter^2;
    % display the results
    metric_string = sprintf('%2.2f',metric);
    % mark objects above the threshold with a black circle
    if metric > threshold
        centroid = stats(k).Centroid;
        plot(centroid(1),centroid(2),'ko');
    end
    text(boundary(1,2)-35,boundary(1,1)+13,metric_string,'Color','y',...
        'FontSize',14,'FontWeight','bold');
end
title(['Metrics closer to 1 indicate that ',...
'the object is approximately round']);

```

Exercise 2. Matlab exercise for selecting grains with a given orientation

Step 1: Read Image

```

I = imread('rice.png');
imshow(I)

```

Step 2: Use Morphological Opening to Estimate the Background

Notice that the background illumination is brighter in the center of the image than at the bottom. Use the IMOPEN function to estimate the background illumination.

```

background = imopen(I,strel('disk',15));
% Display the Background Approximation as a Surface
figure, surf(double(background(1:8:end,1:8:end))),zlim([0 255]);
set(gca,'ydir','reverse');

```

Step 3: Subtract the Background Image from the Original Image

Since the image and background are of class uint8, use the function IMSUBTRACT to subtract the background.

```

I2 = imsubtract(I,background);
imshow(I2)

```

Step 4: Increase the Image Contrast

```

I3 = imadjust(I2);
imshow(I3);

```

Step 5: Threshold the Image

Create a new binary image by thresholding the adjusted image.

```

level = graythresh(I3);
bw = im2bw(I3,level);
imshow(bw)

```

Step 6: Label Objects in the Image

The function BWLABEL labels all connected component in the binary image. The accuracy of your results depend on: the size of the objects, the accuracy of your approximated background, whether you set the connectivity parameter to 4 or 8, whether or not any objects are touching (in which case they may be labeled as one object). Some of the rice grains are touching.

```

[labeled,numObjects] = bwlabel(bw,4); % 4-connected
numObjects % Count all distinct objects in the image.

```

Step 7: Examine the Label Matrix

Each distinct object is labeled with the same integer value. Crop part of a grain that is labeled with 50s.

```

rect = [105 125 10 10];
grain = imcrop(labeled,rect) % Crop a portion of labeled

```

Step 8: View the Whole Label Matrix

A good way to view a label matrix is to display it as a pseudo-color indexed image. In the pseudo-color image, the number that identifies each object in the label matrix maps to a different color in the associated colormap matrix. Use LABEL2RGB to choose the colormap, the background color, and how objects in the label matrix map to colors in the colormap.

```
RGB_label = label2rgb(labeled, @spring, 'c', 'shuffle');  
imshow(RGB_label)
```

Step 9: Measure Object Properties in the Image

The REGIONPROPS command measures object or region properties in an image and returns them in a structure array. When applied to an image with labeled components, it creates one structure element for each component. Use regionprops to create a structure array containing some basic properties for the labeled image.

```
graindata = regionprops(labeled, 'basic')  
% To find the area of the component labeled with 50s, use dot notation to  
% access the Area field in the 50th element in the graindata structure  
% array.  
graindata(50).Area
```

Step 10: Compute Statistical Properties of Objects in the Image

Create a new vector allgrains which holds the area measurement for each grain

```
allgrains = [graindata.Area];  
max_area = max(allgrains) % Find the maximum area of all the grains.  
biggrain = find(allgrains==max_area) % Find the grain number that has this a  
rea.  
mean(allgrains) % Find the mean of the area of all the grains.
```

Step 11: Create a Histogram of the Area of the Grains

```
nbins = 20;  
figure, hist(allgrains, nbins)
```

Step 12: Measure the orientation of the Grains

Now, measure the orientation of each grain

Find out how yourself 😊

Step 13: Select the grains with orientation within 0 and +/-20 degrees

Do it by yourself!

Exercise 3

Use the images circle2.png, circle5.png and circle15.png (from <http://www.uio.no/studier/emner/matnat/ifi/INF4300/h15/undervisningsmateriale>) to evaluate the accuracy of the different formulas for estimation of area and perimeter given in the lecture notes.

Exercise 4: Object features – moments (from 2013-exam)

- How do we define the moments of inertia of an object in a gray level image?

- b) In terms of moments of inertia, what is the requirement for a 2D object to exhibit a unique orientation?
- c) Show the simple relationships between the two moments of inertia μ_{20} and μ_{02} of an image object $f(x,y)$ about axes through its center of mass and the same moments of inertia about the parallel image coordinate axes ($x=0$ and $y=0$).